MODUFLEX VALVE SYSTEM



Full Range Overview





Industrial Communication

V Series








2 Technology Platforms


4/2 valve



The standard 4/2 valves adopt the long life super durable ceramic switching technology

Dual 3/2 &

Dual 4/2 valves



The compact dual 4/2 and 3/2 valves using well proven WCS Parker seal technology



Fitting Clip System

- Short mounting time
- Clear marking

• For the valves, supply module and intermediate

module



For Size 1 & Size 2




For Micro-Moduflex




Tie-Rod and Sub-base

- 2 separate parts for fixation
- Torx T8 screws
- No more aligning of flats
- No over torque
- Easy mounting
- Short assembling time
- Flexible system
- Reinforced sub-bases
- Straight islands
- Reverse compatible






Moduflex Complete Control




Moduflex Adaptative





Complete and Easy Man-Machine dialogue





V Series

Integrated Connection Valve Islands Multi-Wiring or Industrial Communication

Multipole wiring



Sub-D connector

IP depending on femal connector

Guillotine connector IP65



Fieldbus communication















T Series

Traditional Valve Islands



Electrical version ... IP67



... or Pneumatic version

Ø 4 mm built-in connector



S Series

Stand Alone Valves



Electrical version ... IP67



Pneumatic version built-in Ø 4 mm connector



P Series **Peripheral Control Modules**





Dual Flow Control







Ordering Options



Basic Modules

These modules are supplied without connectors, the choice of plug-in connectors enables total flexibility in the field; (Preferred ordering method for best price and delivery.)

Complete Modules

Supplied complete with connectors, for use with valve islands or as stand-alone valves or peripheral modules;

Consult your local distributor or Parker location for Assembly information, price and delivery.







Pre-assembled Valve Islands

Supplied fully assembled to specifications and complete with pneumatic and electrical connectors. Islands can be easily configured with the Moduflex Configurator Software See technical catalogue CD.


Micro-Moduflex

Technologie

Include TWO functions in ONE body :

• 2 x 4/2 valves single solenoid

- High performance sealing :
 - 50 M Cycle





Flow Rate

- Nominal flow rate :
- Qn = 165 NI/min per valve
 - Maximal flow rate :
 - Qmax. = 275 l/mn



> 2m/s

Speed

< 500mm/s













Ø 25 mm Ø 32 mm




Module Width equivalent to Size 1










Price Advantage





Compatibility with MODUFLEX Valve


















Dual 4/2 as Universal Function









Marketing Tools


- Sales Leaflet Moduflex
- Poster
- Technical Catalog (incl manual)
- Configurator CD (can be donwnload from PDE MIS)

Dedicated web page with e-Configurator & CAD generator (from http://www.parker.com/pneu/moduflex & http://www.parker.com/pde/cad)

- Micro-Moduflex dual 4/2 Sales Leaflet
- Torx T8 screw driver
- Demo case
- Design Wins







Any Questions



Many Thanks for your Attention

